



Type	D1	D2	L1	L2	L3	δ	a	R	n
G-80A	150	155	15	50	137	1,50	4	3	3
G-90A	169	175	15	55	142	1,50	4	3	3
G-100A	186	193	15	55	143	1,50	5	3,5	3
G-112A	210	217	17	55	143	1,50	5	3,5	3
G-132A	250	258	17	55	156	1,50	5	3,5	3
G-160A	300	314	20	92	200	2	5	3,5	4
G-180A	340	352	35	118	218	2	5	3,5	4
G-200A	380	393	40	120	225	2	6	4,5	4
G-225A	400	443	45	141	280	2	6	4,5	4
G-250A	4700	482	55	158	300	2	6	4,5	4
G-280A	530	546	65	167	310	2	9	5,5	4
G-315A	600	614	75	175	435	2	9	5,5	4

Type	Voltage	Input power	Speed (r/min)	Input current	Air pressure	Air pressure	Noise	diameter of fan blades
G-80A	Three-phase 380V 50Hz	28	2800	0.07	350	60	52	150
G-90A	Three-phase 380V 50Hz	30	2800	0.07	500	80	55	169
G-100A	Three-phase 380V 50Hz	40	2800	0.14	650	82	57	186
G-112A	Three-phase 380V 50Hz	70	2800	0.21	1000	110	60	250
G-132A	Three-phase 380V 50Hz	55	1450	0.21	880	70	60	300
G-160A	Three-phase 380V 50Hz	60	1400	0.22	1100	40	60	300
G-180A	Three-phase 380V 50Hz	70	1400	0.23	1200	55	60	340
G-200A	Three-phase 380V 50Hz	100	1400	0.31	2500	65	60	380
G-225A	Three-phase 380V 50Hz	135	1400	0.32	3800	80	60	400
G-250A	Three-phase 380V 50Hz	185	1400	0.57	4200	85	62	470
G-280A	Three-phase 380V 50Hz	200	1380	0.64	5000	100	62	530
G-315A	Three-phase 380V 50Hz	500	1350	1,8	6000	150	62	600